

SEMiX305TMLI17E4CV1



SEMiX® 5

3-Level TNPC IGBT-Module

SEMiX305TMLI17E4CV1


Features*

- Solderless assembling solution with PressFIT signal pins and screw power terminals
- IGBT 4 Trench Gate Technology
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Reliable mechanical design with injection moulded terminals and reliable internal connections
- UL recognized file no. E63532
- NTC temperature sensor inside

Remarks*

- Case temperature limited to $T_C=125^\circ\text{C}$ max.
- Product reliability results are valid for $T_{jop}=150^\circ\text{C}$
- IGBT1: outer IGBTs T1 & T4
- IGBT2: inner IGBTs T2 & T3
- Diode1: outer diodes D1 & D4
- Diode2: inner diodes D2 & D3
- Dynamic data are estimated
- For storage and case temperature with TIM see document "TP (HALA P8) SEMiX5p"

Absolute Maximum Ratings				
Symbol	Conditions	Values	Unit	
IGBT1				
V_{CES}		1700	V	
I_C	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	486	A
		$T_c = 80^\circ\text{C}$	376	A
I_{Cnom}		300	A	
I_{CRM}		600	A	
V_{GES}		-20 ... 20	V	
t_{psc}	$V_{CC} = 1000\text{ V}, V_{GE} \leq 15\text{ V}, T_j = 150^\circ\text{C}, V_{CES} \leq 1700\text{ V}$	10	μs	
T_j		-40 ... 175	$^\circ\text{C}$	
IGBT2				
V_{CES}		1200	V	
I_C	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	408	A
		$T_c = 80^\circ\text{C}$	313	A
I_{Cnom}		300	A	
I_{CRM}		600	A	
V_{GES}		-20 ... 20	V	
t_{psc}	$V_{CC} = 800\text{ V}, V_{GE} \leq 15\text{ V}, T_j = 150^\circ\text{C}, V_{CES} \leq 1200\text{ V}$	10	μs	
T_j		-40 ... 175	$^\circ\text{C}$	
Diode1				
V_{RRM}	$T_j = 25^\circ\text{C}$	1700	V	
I_F	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	338	A
		$T_c = 80^\circ\text{C}$	250	A
I_{FRM}		600	A	
I_{FSM}	10 ms, sin 180°, $T_j = 25^\circ\text{C}$	1836	A	
T_j		-40 ... 175	$^\circ\text{C}$	
Diode2				
V_{RRM}	$T_j = 25^\circ\text{C}$	1200	V	
I_F	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	312	A
		$T_c = 80^\circ\text{C}$	232	A
I_{FRM}		600	A	
I_{FSM}	10 ms, sin 180°, $T_j = 25^\circ\text{C}$	1620	A	
T_j		-40 ... 175	$^\circ\text{C}$	
Module				
$I_{t(RMS)}$		400	A	
T_{stg}	module without TIM	-40 ... 125	$^\circ\text{C}$	
V_{isol}	AC sinus 50Hz, t = 1 min	4000	V	



TMLI

SEMiX305TMLI17E4CV1



SEMiX® 5

3-Level TNPC IGBT-Module

SEMiX305TMLI17E4CV1

Features*


- Solderless assembling solution with PressFIT signal pins and screw power terminals
- IGBT 4 Trench Gate Technology
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Reliable mechanical design with injection moulded terminals and reliable internal connections
- UL recognized file no. E63532
- NTC temperature sensor inside

Typical Applications

- UPS
- Solar
- Motor drives

Remarks*

- Case temperature limited to $T_C=125^\circ\text{C}$ max.
- Product reliability results are valid for $T_{jop}=150^\circ\text{C}$
- IGBT1: outer IGBTs T1 & T4
- IGBT2: inner IGBTs T2 & T3
- Diode1: outer diodes D1 & D4
- Diode2: inner diodes D2 & D3
- Dynamic data are estimated
- For storage and case temperature with TIM see document "TP (HALA P8) SEMiX5p"



TMLI

Characteristics				min.	typ.	max.	Unit
Symbol	Conditions						
IGBT1							
$V_{CE(sat)}$	$I_C = 300\text{ A}$ $V_{GE} = 15\text{ V}$ chipllevel	$T_j = 25^\circ\text{C}$	1.90	2.20		V	
		$T_j = 150^\circ\text{C}$	2.30	2.60		V	
V_{CE0}	chipllevel	$T_j = 25^\circ\text{C}$	0.80	0.90		V	
		$T_j = 150^\circ\text{C}$	0.70	0.80		V	
r_{CE}	$V_{GE} = 15\text{ V}$ chipllevel	$T_j = 25^\circ\text{C}$	3.7	4.3		m Ω	
		$T_j = 150^\circ\text{C}$	5.3	6.0		m Ω	
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 12\text{ mA}$		5.2	5.8	6.4	V	
I_{CES}	$V_{GE} = 0\text{ V}, V_{CE} = 1700\text{ V}, T_j = 25^\circ\text{C}$				4.0	mA	
C_{ies}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$		27.2		nF	
C_{oes}		$f = 1\text{ MHz}$		1.06		nF	
C_{res}		$f = 1\text{ MHz}$		0.88		nF	
Q_G	$V_{GE} = -8\text{ V}...+15\text{ V}$			2400		nC	
R_{Gint}	$T_j = 25^\circ\text{C}$			2.1		Ω	
$t_{d(on)}$	$V_{CC} = 1200\text{ V}$	$T_j = 150^\circ\text{C}$		135		ns	
t_r	$I_C = 300\text{ A}$	$T_j = 150^\circ\text{C}$		73		ns	
E_{on}	$V_{GE} = +15/-15\text{ V}$	$T_j = 150^\circ\text{C}$		38		mJ	
$t_{d(off)}$	$R_{G on} = 1\ \Omega$	$T_j = 150^\circ\text{C}$		583		ns	
t_f	$R_{G off} = 1\ \Omega$	$T_j = 150^\circ\text{C}$		139		ns	
E_{off}	$di/dt_{on} = 3765\text{ A}/\mu\text{s}$ $di/dt_{off} = 1725\text{ A}/\mu\text{s}$ $dv/dt = 3962\text{ V}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		60		mJ	
		$T_j = 150^\circ\text{C}$					
$R_{th(j-c)}$	per IGBT				0.08	K/W	
$R_{th(c-s)}$	per IGBT ($\lambda_{grease}=0.81\text{ W}/(\text{m}^*\text{K})$)			0.03		K/W	
$R_{th(c-s)}$	per IGBT, pre-applied phase change material			0.02		K/W	
IGBT2							
$V_{CE(sat)}$	$I_C = 300\text{ A}$ $V_{GE} = 15\text{ V}$ chipllevel	$T_j = 25^\circ\text{C}$	1.80	2.05		V	
		$T_j = 150^\circ\text{C}$	2.20	2.40		V	
V_{CE0}	chipllevel	$T_j = 25^\circ\text{C}$	0.80	0.90		V	
		$T_j = 150^\circ\text{C}$	0.70	0.80		V	
r_{CE}	$V_{GE} = 15\text{ V}$ chipllevel	$T_j = 25^\circ\text{C}$	3.3	3.8		m Ω	
		$T_j = 150^\circ\text{C}$	5.0	5.3		m Ω	
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 12\text{ mA}$		5	5.8	6.5	V	
I_{CES}	$V_{GE} = 0\text{ V}, V_{CE} = 1200\text{ V}, T_j = 25^\circ\text{C}$				4.0	mA	
C_{ies}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$		18.6		nF	
C_{oes}		$f = 1\text{ MHz}$		1.16		nF	
C_{res}		$f = 1\text{ MHz}$		1.02		nF	
Q_G	$V_{GE} = -8\text{ V}...+15\text{ V}$			1700		nC	
R_{Gint}	$T_j = 25^\circ\text{C}$			2.5		Ω	
$t_{d(on)}$	$V_{CC} = 1200\text{ V}$	$T_j = 150^\circ\text{C}$		94		ns	
t_r	$I_C = 300\text{ A}$	$T_j = 150^\circ\text{C}$		75		ns	
E_{on}	$V_{GE} = +15/-8\text{ V}$	$T_j = 150^\circ\text{C}$		42		mJ	
$t_{d(off)}$	$R_{G on} = 1\ \Omega$	$T_j = 150^\circ\text{C}$		481		ns	
t_f	$R_{G off} = 1\ \Omega$	$T_j = 150^\circ\text{C}$		124		ns	
E_{off}	$di/dt_{on} = 3415\text{ A}/\mu\text{s}$ $di/dt_{off} = 2153\text{ A}/\mu\text{s}$ $dv/dt = 5133\text{ V}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		35		mJ	
		$T_j = 150^\circ\text{C}$					
$R_{th(j-c)}$	per IGBT				0.12	K/W	
$R_{th(c-s)}$	per IGBT ($\lambda_{grease}=0.81\text{ W}/(\text{m}^*\text{K})$)			0.048		K/W	
$R_{th(c-s)}$	per IGBT, pre-applied phase change material			0.023		K/W	

SEMiX305TMLI17E4CV1



SEMiX® 5

3-Level TNPC IGBT-Module


SEMiX305TMLI17E4CV1

Features*

- Solderless assembling solution with PressFIT signal pins and screw power terminals
- IGBT 4 Trench Gate Technology
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Reliable mechanical design with injection moulded terminals and reliable internal connections
- UL recognized file no. E63532
- NTC temperature sensor inside

Remarks*

- Case temperature limited to $T_C=125^\circ\text{C}$ max.
- Product reliability results are valid for $T_{jop}=150^\circ\text{C}$
- IGBT1: outer IGBTs T1 & T4
- IGBT2: inner IGBTs T2 & T3
- Diode1: outer diodes D1 & D4
- Diode2: inner diodes D2 & D3
- Dynamic data are estimated
- For storage and case temperature with TIM see document "TP (HALA P8) SEMiX5p"



TMLI

Characteristics							
Symbol	Conditions		min.	typ.	max.	Unit	
Diode1							
$V_F = V_{EC}$	$I_F = 300\text{ A}$ $V_{GE} = 0\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	2.00	2.40		V	
		$T_j = 150^\circ\text{C}$	2.14	2.56		V	
V_{F0}	chipelevel	$T_j = 25^\circ\text{C}$	1.32	1.56		V	
		$T_j = 150^\circ\text{C}$	1.08	1.22		V	
r_F	chipelevel	$T_j = 25^\circ\text{C}$	2.3	2.8		m Ω	
		$T_j = 150^\circ\text{C}$	3.5	4.5		m Ω	
I_{RRM}	$I_F = 300\text{ A}$	$T_j = 150^\circ\text{C}$	216.2			A	
Q_{rr}	$di/dt_{off} = 3415\text{ A}/\mu\text{s}$ $V_{CC} = 1200\text{ V}$	$T_j = 150^\circ\text{C}$	88.7			μC	
E_{rr}	$V_{GE} = +15/-15\text{ V}$	$T_j = 150^\circ\text{C}$	38			mJ	
$R_{th(j-c)}$	per diode				0.17	K/W	
$R_{th(c-s)}$	per diode ($\lambda_{grease}=0.81\text{ W}/(\text{m}^2\text{K})$)			0.04		K/W	
$R_{th(c-s)}$	per diode, pre-applied phase change material			0.035		K/W	
Diode2							
$V_F = V_{EC}$	$I_F = 300\text{ A}$ $V_{GE} = 0\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	2.14	2.46		V	
		$T_j = 150^\circ\text{C}$	2.07	2.38		V	
V_{F0}	chipelevel	$T_j = 25^\circ\text{C}$	1.30	1.50		V	
		$T_j = 150^\circ\text{C}$	0.90	1.10		V	
r_F	chipelevel	$T_j = 25^\circ\text{C}$	2.8	3.2		m Ω	
		$T_j = 150^\circ\text{C}$	3.9	4.3		m Ω	
I_{RRM}	$I_F = 300\text{ A}$	$T_j = 150^\circ\text{C}$	194.6			A	
Q_{rr}	$di/dt_{off} = 3765\text{ A}/\mu\text{s}$ $V_R = 1200\text{ V}$	$T_j = 150^\circ\text{C}$	37.8			μC	
E_{rr}	$V_{GE} = +15/-8\text{ V}$	$T_j = 150^\circ\text{C}$	13			mJ	
$R_{th(j-c)}$	per diode				0.21	K/W	
$R_{th(c-s)}$	per diode ($\lambda_{grease}=0.81\text{ W}/(\text{m}^2\text{K})$)			0.058		K/W	
$R_{th(c-s)}$	per diode, pre-applied phase change material			0.043		K/W	
Module							
L_{sCE1}				31		nH	
L_{CE}				42		nH	
R_{CC+EE}	measured between terminal 5 and 1	$T_C = 25^\circ\text{C}$	0.8			m Ω	
		$T_C = 125^\circ\text{C}$	1.1			m Ω	
$R_{th(c-s)1}$	calculated without thermal coupling			0.005		K/W	
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module, P12 (reference)			0.009		K/W	
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module, pre-applied phase change material			0.006		K/W	
M_s	to heat sink (M5)		3		6	Nm	
M_t			to terminals (M6)		3	6	Nm
							Nm
w				398		g	
Temperature Sensor							
R_{100}	$T_C=100^\circ\text{C}$ ($R_{25}=5\text{ k}\Omega$)			$493 \pm 5\%$		Ω	
$B_{100/125}$	$R_{(T)}=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$; $T[\text{K}]$;			$3550 \pm 2\%$		K	




Fig. 1: Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2: IGBT1 rated current vs. Temperature $I_C=f(T_C)$




Fig. 3: Typ. IGBT1 & Diode2 turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. IGBT1 & Diode2 turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. IGBT1 transfer characteristic










Fig. 6: Typ. IGBT1 gate charge characteristic






Fig. 15: Typ. IGBT2 & Diode1 turn-on /-off energy = $f(I_C)$




Fig. 16: Typ. IGBT2 & Diode1 turn-on / -off energy = $f(R_G)$




Fig. 17: Typ. IGBT2 transfer characteristic




Fig. 18: Typ. IGBT2 gate charge characteristic




Fig. 19: Typ. IGBT2 switching times vs. I_C




Fig. 20: Typ. IGBT2 switching times vs. gate resistor R_G




Fig. 21: Transient thermal impedance of IGBT2 & Diode1






Fig. 22: Diode1 forward characteristic


SEMiX305TMLI17E4CV1



* = Dimensions in mm with tolerance of ± 0.4

For technical details please refer
to SEMiX(R)5 Mounting Instruction

SEMiX5p



TMLI

IMPORTANT INFORMATION AND WARNINGS

This is an electrostatic discharge sensitive device (ESDS) according to international standard IEC 61340.

*The specifications of Semikron Danfoss products may not be considered as any guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of Semikron Danfoss products describe only the usual characteristics of Semikron Danfoss products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Resulting from this, application adjustments of any kind may be necessary. Any user of Semikron Danfoss products is responsible for the safety of their applications embedding Semikron Danfoss products and must take adequate safety measures to prevent the applications from causing any physical injury, fire or other problem, also if any Semikron Danfoss product becomes faulty. Any user is responsible for making sure that the application design and realization are compliant with all laws, regulations, norms and standards applicable to the scope of application. Unless otherwise explicitly approved by Semikron Danfoss in a written document signed by authorized representatives of Semikron Danfoss, Semikron Danfoss products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. Semikron Danfoss does not convey any license under its or a third party's patent rights, copyrights, trade secrets or other intellectual property rights, neither does it make any representation or warranty of non-infringement of intellectual property rights of any third party which may arise from a user's applications.