

SK 150 DGL 12T4



SEMITOP® 3

3-phase bridge rectifier + brake chopper

SK 150 DGL 12T4

Features*


- Compact design
- One screw mounting
- Heat transfer and insulation through direct copper bonded aluminum oxide ceramic (DBC)
- 1200V Trench4 IGBT technology
- CAL diode technology for FWD and APD
- UL file recognized, file no E63-532

Typical Applications

- Rectifier
- Motor Drive

Remarks

- Diode1 = Rectifier Diode
- Diode2 = Free Wheeling Diode
- Diode3 = Anti Parallel Diode



DGL

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT 1				
V_{CES}	$T_j = 25\text{ °C}$		1200	V
I_C	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	55	A
		$T_s = 70\text{ °C}$	42	A
I_C	$T_j = 175\text{ °C}$	$T_s = 25\text{ °C}$	61	A
		$T_s = 70\text{ °C}$	50	A
I_{Chom}			50	A
I_{CRM}			150	A
V_{GES}			-20 ... 20	V
t_{psc}	$V_{CC} = 800\text{ V}$ $V_{GE} \leq 15\text{ V}$ $V_{CES} \leq 1200\text{ V}$	$T_j = 150\text{ °C}$	10	μs
T_j			-40 ... 175	$^{\circ}\text{C}$

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
Rectifier				
V_{RSM}	$T_j = 25\text{ °C}$		1300	V
V_{RRM}	$T_j = 25\text{ °C}$		1200	V
I_D	rec 120° $T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	138	A
		$T_s = 70\text{ °C}$	105	A
I_{FSM}	sin 180° 10 ms	$T_j = 25\text{ °C}$	635	A
		$T_j = 150\text{ °C}$	490	A
i^2t	sin 180° 10 ms	$T_j = 25\text{ °C}$	2016	A^2s
		$T_j = 150\text{ °C}$	1200	A^2s
T_j			-40 ... 150	$^{\circ}\text{C}$

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
Diode 2				
V_{RRM}	$T_j = 25\text{ °C}$		1200	V
I_F	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	25	A
		$T_s = 70\text{ °C}$	19	A
I_F	$T_j = 175\text{ °C}$	$T_s = 25\text{ °C}$	28	A
		$T_s = 70\text{ °C}$	22	A
I_{FRM}			50	A
I_{FSM}	10 ms sin 180°	$T_j = 25\text{ °C}$	100	A
		$T_j = 150\text{ °C}$	100	A
T_j			-40 ... 175	$^{\circ}\text{C}$

SK 150 DGL 12T4



SEMITOP® 3

3-phase bridge rectifier +
brake chopper

SK 150 DGL 12T4

Features*

- Compact design
- One screw mounting
- Heat transfer and insulation through direct copper bonded aluminum oxide ceramic (DBC)
- 1200V Trench4 IGBT technology
- CAL diode technology for FWD and APD
- UL file recognized, file no E63-532

Typical Applications

- Rectifier
- Motor Drive


Remarks

- Diode1 = Rectifier Diode
- Diode2 = Free Wheeling Diode
- Diode3 = Anti Parallel Diode

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
Diode 3				
V_{RRM}	$T_j = 25\text{ °C}$		1200	V
I_F	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	13	A
		$T_s = 70\text{ °C}$	10	A
I_F	$T_j = 175\text{ °C}$	$T_s = 25\text{ °C}$	15	A
		$T_s = 70\text{ °C}$	12	A
I_{FRM}			16	A
I_{FSM}	10 ms	$T_j = 25\text{ °C}$	36	A
	sin 180°	$T_j = 150\text{ °C}$	36	A
T_j			-40 ... 175	°C

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
Module				
$I_{t(RMS)}$	$\Delta T_{\text{terminal}}$ at PCB joint = 30 K, per pin		60	A
T_{stg}	module without TIM		-40 ... 125	°C
V_{isol}	AC, sinusoidal, t = 1 min		2500	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT 1						
$V_{CE(sat)}$	$I_C = 50\text{ A}$ $V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25\text{ °C}$	1.85	2.10		V
		$T_j = 150\text{ °C}$	2.20	2.40		V
V_{CE0}	chipelevel	$T_j = 25\text{ °C}$	0.80	0.90		V
		$T_j = 150\text{ °C}$	0.70	0.80		V
r_{CE}	$V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25\text{ °C}$	21	24		mΩ
		$T_j = 150\text{ °C}$	30	32		mΩ
$V_{GE(th)}$	$V_{GE} = V_{GE} = V_{CE}, I_C = 1.7\text{ mA}$		5	5.8	6.5	V
I_{CES}	$V_{GE} = 0\text{ V}, V_{CE} = 1200\text{ V}, T_j = 25\text{ °C}$				1	mA
C_{ies}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$	2.77			nF
C_{oes}		$f = 1\text{ MHz}$	0.21			nF
C_{res}		$f = 1\text{ MHz}$	0.16			nF
Q_G	$V_{GE} = -15\text{ V} \dots +15\text{ V}$			333		nC
R_{Gint}	$T_j = 25\text{ °C}$			4.0		Ω
$t_{d(on)}$	$V_{CC} = 600\text{ V}$	$T_j = 150\text{ °C}$		130		ns
t_r	$I_C = 50\text{ A}$ $V_{GE\ neg} = -15\text{ V}$ $V_{GE\ pos} = 15\text{ V}$	$T_j = 150\text{ °C}$		42		ns
		$T_j = 150\text{ °C}$		4.8		mJ
E_{on}	$R_{G\ on} = 15\text{ Ω}$	$T_j = 150\text{ °C}$		330		ns
$t_{d(off)}$		$T_j = 150\text{ °C}$		65		ns
t_f	$R_{G\ off} = 15\text{ Ω}$	$T_j = 150\text{ °C}$		65		ns
E_{off}	$di/dt_{on} = 2100\text{ A}/\mu\text{s}$ $di/dt_{off} = 920\text{ A}/\mu\text{s}$ $dv/dt = 4000\text{ V}/\mu\text{s}$	$T_j = 150\text{ °C}$		5		mJ
$R_{th(j-s)}$	per IGBT, $\lambda_{paste} = 0.8\text{ W}/(\text{mK})$			0.85		K/W



DGL

SK 150 DGL 12T4



SEMITOP® 3

3-phase bridge rectifier + brake chopper

SK 150 DGL 12T4

Features*


- Compact design
- One screw mounting
- Heat transfer and insulation through direct copper bonded aluminum oxide ceramic (DBC)
- 1200V Trench4 IGBT technology
- CAL diode technology for FWD and APD
- UL file recognized, file no E63-532

Typical Applications

- Rectifier
- Motor Drive

Remarks

- Diode1 = Rectifier Diode
- Diode2 = Free Wheeling Diode
- Diode3 = Anti Parallel Diode



DGL

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Diode 1						
V_F	$I_F = 25\text{ A}$	$T_j = 25\text{ °C}$		1.00	1.21	V
	chipelevel	$T_j = 125\text{ °C}$		0.90	1.10	V
V_{F0}	chipelevel	$T_j = 25\text{ °C}$		0.88	0.98	V
		$T_j = 125\text{ °C}$		0.73	0.83	V
r_F	chipelevel	$T_j = 25\text{ °C}$		4.8	9.2	mΩ
		$T_j = 125\text{ °C}$		6.8	11	mΩ
I_R	$T_j = 145\text{ °C}, V_{RRM}$				2	mA
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=0.8\text{ W/(mK)}$			1.2		K/W

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Diode 2						
V_F	$I_F = 25\text{ A}$	$T_j = 25\text{ °C}$		2.41	2.74	V
	chipelevel	$T_j = 150\text{ °C}$		2.45	2.79	V
V_{F0}	chipelevel	$T_j = 25\text{ °C}$		1.30	1.50	V
		$T_j = 150\text{ °C}$		0.90	1.10	V
r_F	chipelevel	$T_j = 25\text{ °C}$		44	50	mΩ
		$T_j = 150\text{ °C}$		62	68	mΩ
I_{RRM}	$I_F = 50\text{ A}$	$T_j = 150\text{ °C}$		45		A
Q_{rr}	$di/dt_{off} = 2100\text{ A}/\mu\text{s}$	$T_j = 150\text{ °C}$		1.8		μC
E_{rr}	$V_{GE} = -15\text{ V}$ $V_{CC} = 600\text{ V}$	$T_j = 150\text{ °C}$		1		mJ
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=0.8\text{ W/(mK)}$			1.9		K/W

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Diode 3						
V_F	$I_F = 8\text{ A}$	$T_j = 25\text{ °C}$		2.33	2.65	V
	chipelevel	$T_j = 150\text{ °C}$		2.35	2.68	V
V_{F0}	chipelevel	$T_j = 25\text{ °C}$		1.30	1.50	V
		$T_j = 150\text{ °C}$		0.90	1.10	V
r_F	chipelevel	$T_j = 25\text{ °C}$		129	144	mΩ
		$T_j = 150\text{ °C}$		181	198	mΩ
I_{RRM}	$I_F = 8\text{ A}$			-		A
Q_{rr}				-		μC
E_{rr}	$V_{CC} = 600\text{ V}$			-		mJ
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=0.8\text{ W/(mK)}$			2.7		K/W

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Module						
M_s	to heatsink		2.25		2.5	Nm
w	weight			29		g




Fig. 1: Typ. IGBT1 output characteristic, incl. $R_{CC'+EE'}$




Fig. 2: Typ. rated current vs. temperature $I_C = f(T_s)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 9: Typ. Transient thermal impedance of IGBT1 & Diode2





Fig. 10: Typ. Diode2 forward characteristic, incl. $R_{CC'+EE'}$

SK 150 DGL 12T4

Dimensions: mm

Tolerance system: ISO 2768-m




Suggested drilled hole diameter for terminal pins in the circuit board:

- refer Mounting Instruction SEMITOP® Classic

These documents are SEMIKRON properties. SEMIKRON reserves all copyrights. All copying and transmitting of this information requires written permission. For the case of industrial property rights, SEMIKRON reserves all rights.

SEMITOP®3



DGL

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.