


SEMiX106GD12M7p



IGBT Modules

SEMiX106GD12M7p

Features*


- Press Fit
- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High overload capability
- Low loss high density IGBTs
- UL recognized file no. E63532

Typical Applications

- AC inverter drives
- UPS
- Electronic Welding

Remarks


- Case temperature limited to $T_C=125^\circ\text{C}$ max.
- V_{isol} between temperature sensor and power section is only 2500V
- Product reliability results valid for $T_j \leq 150^\circ\text{C}$ (recommended $T_{jop} = -40 \dots 150^\circ\text{C}$)



Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT				
V _{CES}	T _j = 25 °C		1200	V
I _C	T _j = 175 °C	T _c = 25 °C	164	A
		T _c = 80 °C	125	A
I _{Cnom}			100	A
I _{CRM}			200	A
V _{GES}			-20 ... 20	V
t _{psc}	V _{CC} = 600 V V _{GE} ≤ 15 V V _{CES} ≤ 1200 V	T _j = 150 °C	8	µs
T _j			-40 ... 175	°C
Inverse diode				
V _{RRM}	T _j = 25 °C		1200	V
I _F	T _j = 175 °C	T _c = 25 °C	121	A
		T _c = 80 °C	91	A
I _{FRM}			200	A
I _{FSM}	t _p = 10 ms, sin 180°, T _j = 25 °C		550	A
T _j			-40 ... 175	°C
Module				
I _{t(RMS)}	per connector pin		50	A
T _{stg}			-40 ... 125	°C
V _{isol}	AC sinus 50Hz, t = 1 min		4000	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
V _{CE(sat)}	I _C = 100 A	T _j = 25 °C		1.55	1.85	V
	V _{GE} = 15 V chipelevel	T _j = 150 °C		1.75	2.09	V
V _{CE0}	chipelevel	T _j = 25 °C		0.85	1.00	V
		T _j = 150 °C		0.75	0.90	V
r _{CE}	V _{GE} = 15 V	T _j = 25 °C		7.0	8.5	mΩ
	chipelevel	T _j = 150 °C		10	12	mΩ
V _{GE(th)}	V _{CE} = 10 V, I _C = 10 mA		5.4	6	6.6	V
I _{CES}	V _{GE} = 0 V, V _{CE} = 1200 V, T _j = 25 °C				1.0	mA
C _{ies}	V _{CE} = 10 V V _{GE} = 0 V	f = 1 MHz		21.0		nF
C _{oes}		f = 1 MHz		0.60		nF
C _{res}		f = 1 MHz		0.28		nF
Q _G	V _{GE} = -8V ... + 15V			1000		nC
R _{Gint}	T _j = 25 °C			0.0		Ω
t _{d(on)}	V _{CC} = 600 V	T _j = 150 °C		48		ns
t _r	I _C = 100 A	T _j = 150 °C		21		ns
E _{on}	V _{GE} = +15/-15 V R _{G on} = 3.6 Ω	T _j = 150 °C		8.5		mJ
t _{d(off)}	R _{G off} = 3.6 Ω	T _j = 150 °C		261		ns
t _f	di/dt _{on} = 4500 A/μs di/dt _{off} = 1400 A/μs	T _j = 150 °C		58		ns
E _{off}	dv/dt = 5400 V/μs L _s = 25 nH	T _j = 150 °C		11		mJ
R _{th(j-c)}	per IGBT				0.31	K/W
R _{th(c-s)}	per IGBT (λ _{grease} =0.81 W/(m*K))			0.060		K/W

SEMiX106GD12M7p



SEMiX® 6p

IGBT Modules

SEMiX106GD12M7p

Features*

- Press Fit
- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High overload capability
- Low loss high density IGBTs
- UL recognized file no. E63532


Typical Applications

- AC inverter drives
- UPS
- Electronic Welding

Remarks

- Case temperature limited to $T_C=125^\circ\text{C}$ max.
- V_{isol} between temperature sensor and power section is only 2500V
- Product reliability results valid for $T_j \leq 150^\circ\text{C}$ (recommended $T_{jop} = -40 \dots 150^\circ\text{C}$)

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverse diode						
V _F = V _{EC}	I _F = 100 A	T _j = 25 °C		2.20	2.52	V
	V _{GE} = 0 V chiplevel	T _j = 150 °C		2.20	2.47	V
V _{F0}	chiplevel	T _j = 25 °C		1.30	1.50	V
		T _j = 150 °C		0.90	1.10	V
r _F	chiplevel	T _j = 25 °C		9.0	10	mΩ
		T _j = 150 °C		13	14	mΩ
I _{RRM}	I _F = 100 A	T _j = 150 °C		160		A
Q _{rr}	di/dt _{off} = 5500 A/μs	T _j = 150 °C		17		μC
E _{rr}	V _{GE} = -15 V V _{CC} = 600 V	T _j = 150 °C		7.5		mJ
R _{th(j-c)}	per diode				0.48	K/W
R _{th(c-s)}	per diode (λ _{grease} =0.81 W/(m*K))			0.080		K/W
Module						
L _{CE}				18		nH
R _{CC'+EE'}	measured per switch	T _C = 25 °C		1		mΩ
		T _C = 125 °C		1.4		mΩ
R _{th(c-s)1}	calculated without thermal coupling (λ _{grease} =0.81 W/(m*K))			0.006		K/W
R _{th(c-s)2}	including thermal coupling, T _s underneath module (λ _{grease} =0.81 W/ (m*K))			0.009		K/W
M _s	to heat sink (M5)		3		6	Nm
M _t				-		Nm
				-		Nm
w				300		g
Temperature Sensor						
R ₁₀₀	T _C =100°C (R ₂₅ =5 kΩ)			493 ± 5%		Ω
B _{100/125}	R(T)=R ₁₀₀ exp[B _{100/125} (1/T-1/T ₁₀₀)]; T[K];			3550 ±2%		K



GD




Fig. 1: Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2: IGBT rated current vs. temperature $I_C=f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Transient thermal impedance




Fig. 10: Typ. CAL diode forward charact., incl. $R_{CC'+EE'}$




Fig. 11: Typ. CAL diode peak reverse recovery current









Fig. 12: Typ. CAL diode recovery charge




Cross-sectional plane in the middle of the module



Cut-out shows section through the center of the PCB-dome





IMPORTANT INFORMATION AND WARNINGS

This is an electrostatic discharge sensitive device (ESDS) according to international standard IEC 61340.

*The specifications of Semikron Danfoss products may not be considered as any guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of Semikron Danfoss products describe only the usual characteristics of Semikron Danfoss products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Resulting from this, application adjustments of any kind may be necessary. Any user of Semikron Danfoss products is responsible for the safety of their applications embedding Semikron Danfoss products and must take adequate safety measures to prevent the applications from causing any physical injury, fire or other problem, also if any Semikron Danfoss product becomes faulty. Any user is responsible for making sure that the application design and realization are compliant with all laws, regulations, norms and standards applicable to the scope of application. Unless otherwise explicitly approved by Semikron Danfoss in a written document signed by authorized representatives of Semikron Danfoss, Semikron Danfoss products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. Semikron Danfoss does not convey any license under its or a third party's patent rights, copyrights, trade secrets or other intellectual property rights, neither does it make any representation or warranty of non-infringement of intellectual property rights of any third party which may arise from a user's applications.